

SUBMITTAL DATA: BCAS12HPJ1CA		12000 BTU/H Cassette Heat Pump System
Job Name	Location	Date
Purchaser	Engineer	
Submitted To	For	
Unit Designation	Schedule No.	

BCAS12HPJ1CA	KULA12HPJ10A
--------------	--------------



GENERAL FEATURES

- High Efficiency DC Inverter
- Technology Compact and Quiet Design
- 4 - Way Discharge Air
- Internal Condensate Drain Pump
- Wireless Remote with LCD Display Included
- XK19 Wired Controller Included
- Low Ambient Cooling down to -20°F (Range -20°F to 122°F)
- Low Ambient Heating down to -22°F (Range -22°F to 86°F)
- Coil (Indoor and Outdoor) Copper Tube / Aluminum Fin*
- * (Blue Fin) 500 Hrs Salt Spray Tested



SPECIFICATIONS		KULA12HPJ10A / BCAS12HPJ1CA	
System Type		HEAT PUMP	
SYSTEM PERFORMANCE			
Cooling	Rated Capacity @ 95°F	Btu/h	12000
	Min-Max Capacity	Btu/h	900 - 14100
	Rated Power Input (Min - Max)	W	
Heating	Rated Capacity @ 47°F	Btu/h	12000
	Rated Capacity @ 17°F	Btu/h	6900
	Min-Max Capacity	Btu/h	900 - 15500
	Rated Power Input (Min - Max)	W	
SEER / EER		24 / 13	
HSPF / COP		11.3 / 4.0	
Energy Star®		YES	
Cooling Temperature Range		°F	-20 - 122
Heating Temperature Range		°F	-22 - 86
INDOOR UNIT		BCAS12HPJ1CA	
Fan Motor Output Power		W	45
Fan Motor FLA		amps	0.5
Air Flow (Min - Max)		CFM	265 - 383
Sound Pressure Level (Cooling / Heating)		dB(A)	34 -44
Dehumidification		pt/hr	2.96
Condensate Drain Size (OD)		in	1
Unit Dimension (WxHxD)		in	23 1/2 X 23 1/2 X 9 1/2
Package Dimension (WxHxD)		in	30 1/2 X 29 X 11 1/4
Weight (Net / Gross)		lbs	44 /53
OUTDOOR UNIT		KULA12HPJ10A	
Compressor Type		G-10 / 1-Stage Inverter	
Compressor RLA		amps	6.6
Fan Motor Output Power		W	30
Fan Motor RLA		amps	0.37
Sound Pressure Level (Cooling / Heating)		dB(A)	52
Unit Dimension (WxHxD)		in	35 3/8 X 23 1/2 X 14 7/8
Package Dimension (WxHxD)		in	37 3/16 X 24 7/8 X 16 1/2
Weight (Net / Gross)		lbs	83.8/90.4
Refrigerant Charge - R410A		oz	47.3
Coil Type		Aluminum Fin / Copper Tube	
REFRIGERANT PIPING			
Indoor Service Valve Size (Liquid - Gas)		in	1/4 - 3/8
Outdoor Service Valve Size (Liquid - Gas)		in	1/4 - 3/8
Pre-Charge Lengh		ft	25
Pipe Length (Min - Max)		ft	10 / 66
Max. Pipe Elevation		ft	33
ELECTRICAL			
Power Supply (Voltage Operating Range)		208-230V / 1Ph / 60Hz	
Rated Current (Cooling / Heating)		amps	4 / 7.5
MCA / MOCp		amps	10 / 15
Main Power Wire Size		AWG	Size Per Local Code
Interconnecting Wire Size		AWG	14 / 4

EXTENDED RATINGS

BCAS12HPJ1CA

COOLING PERFORMANCE						HEATING PERFORMANCE					
Outdoor Ambient Temperature (DB)		Return Air Temperature				Outdoor Ambient Temperature (DB)		Return Air Temperature			
		80°F (DB)						70°F (DB)			
		TC (Btu/h)	SHR	EER	Power Input (W)			TC (Btu/h)	COP	Power Input (W)	
MAX OUTPUT	-20°F					MAX OUTPUT	-22°F				
	-15°F						-20°F				
	-10°F						-15°F	5140	1.44	1046	
	-5°F	5820	4210	3.25	525		-10°F	5460	1.51	1062	
	0°F	5990	4350	3.26	539		-5°F	5760	1.57	1077	
	5°F	6230	4555	3.32	550		0°F	7800	2.09	1096	
	10°F	6400	4700	3.31	567		5°F	8990	2.36	1116	
	15°F	6570	4851	3.30	584		10°F	9600	2.61	1077	
	20°F	6900	5090	3.34	605		15°F	10140	2.77	1072	
	25°F	7200	5320	3.37	627		17°F	10670	2.93	1067	
	30°F	7680	5722	3.41	660		20°F	10800	3.11	1019	
	35°F	8020	6011	3.42	688		25°F	10920	3.23	989	
	40°F	8390	6300	3.44	715		30°F	11160	3.34	980	
	45°F	8760	6593	3.31	776		35°F	11280	3.46	955	
	50°F	9110	6886	3.19	836		40°F	11400	3.59	931	
	55°F	9420	7130	3.22	858		45°F	11760	3.63	951	
	60°F	9720	7387	3.24	880		47°F	11870	3.62	961	
	65°F	10360	7916	3.25	935		50°F	12000	3.63	970	
	70°F	11040	8440	3.27	990		55°F	12960	3.80	999	
	75°F	12110	9332	3.40	1045		60°F	13800	3.93	1028	
	80°F	12600	9735	3.48	1062		65°F	13200	3.65	1059	
	85°F	13070	10137	3.55	1079		70°F	12700	3.49	1067	
	90°F	12530	9720	3.37	1089		75°F	11880	3.23	1077	
	95°F	12000	9360	3.20	1100		80°F	11160	3.12	1048	
	100°F	11390	8919	2.92	1144		86°F	10350	2.91	1042	
	105°F	10800	8470	2.66	1188						
	110°F	10420	8221	2.49	1228						
	115°F	10050	7960	2.33	1265						
	120°F	9450	7511	2.18	1271						
	122°F	8870	7050	2.03	1279						


LEGEND: W - Watts
 DB - Dry Bulb
 TC - Total Capacity
 SHR - Sensible Heat Ratio
 COP - Coeffecient of Performance

FEATURES & FUNCTIONS SUMMARY**KULA12HPJ10A / BCAS12HPJ1CA****SYSTEM FEATURES**



Inverter Type	G10
Ultra Low Frequency Torque Control	Yes
Power Factor Correction	Yes
Compressor Type - Inverter	High Efficiency Rotary
Basepan With Electric Heater	Yes
Indoor & Outdoor Fin Coating	Yes
Intelligent Defrosting	Yes
Intelligent Preheating	Yes
Low Voltage Startup	Yes
Memory/Power Failure Recovery	Yes
Self Diagnosis	Yes
Wired Controller Interface	Yes
WiFi Included	No
Indoor Fan Type	Centrifugal
Multi Fan Speeds	4 Speeds
Indoor Unit Display	Yes
Auxiliary Electrical Heater	No
Ventilation (Outdoor Air)	No

REMOTE CONTROLLER FUNCTIONS

Auto Mode	Yes
Auto Fan	Yes
Auto Swing (Horizontal Auto Swing)	No
Auto Swing (Vertical Auto Swing)	Yes
Clock	Yes
Dry Mode	Yes
Dry Anti-Mildew (X-Fan) Mode	Yes
Energy Saving Mode	Yes
Dirty Filter Alert	No
Fan Speed Control (7 Speeds)	Yes
I Feel Function	Yes
Privacy Lock	Yes
Quiet Mode	No
Room Temperature Display	No
Sleep Mode	Yes
Normal Sleep Mode Option	Yes
Timer Mode	Yes
Turbo Mode	Yes
Display On/Off Control	Yes
Freeze Guard Mode	Yes
Power Failure Mode	Yes





Dimensions	
A	26 3/8
B	26 3/8
C	23 5/8
D	19 1/2
E	5 11/16
F	9 7/16
G	23 1/2



Clearances	
A	7/8
B	60
C	98
H	10


DIMENSIONS & CLEARANCES

KULA12HPJ10A



Dimensions	
A	30 3/4
B	33 3/8
C	23 1/2
D	10 1/8
E	12 5/8
F	21 5/16
G	11 5/16

Unit: inch



Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.